

FORESTRY TILLERS

SSL

Forestry tiller for PTO tractors with fixed teeth rotor.

This is the smallest model in FAE's line of Forestry Tillers. Thanks to its low weight and multiple working width options, the SSL fits a wide range of tractors. The transmission with side gearbox allows the rotor

to spin at a lower rpm than a traditional belt driven mulcher. This makes the transmission much more reliable, and ensures a deep, consistent grinding while also lowering tool wear.



100-220 hp



Ø 30 cm max



Depth 30 cm



Reinforced hydraulic hood helps provide a finer product while being more durable



Dual transmission with side gearbox increase power delivery to the rotor



STANDARD EQUIPMENT

Hydraulic rear hood	Gearbox with freewheel
Enclosed machine body	Friction clutches (SSL/DT)
Inside lateral protection	PTO shaft with cam clutch
Protection chains	Bolted-on rotor shafts (in forged steel)
Transmission with side gearbox	Flat pressed welded steel counter-blades

OPTIONS

Multiple tooth options	Hydraulic support roller
Hydraulic top link	Two disc front plows

MODEL	SSL-150	SSL-175	SSL/DT-200	SSL/DT-225	SSL/DT-250
Tractor (hp)	100-160	110-160	120-220	130-220	140-220
PTO (rpm)	1000	1000	1000	1000	1000
Working width (mm)	1600	1840	2080	2320	2560
Total width (mm)	1920	2160	2400	2640	2880
Weight (kg)	2080	2260	2620	2810	2990
Rotor diameter (mm)	600	600	600	600	600
Max shredding diameter (mm)	300	300	300	300	300
Max working depth (mm)	300	300	300	300	300
No. teeth type B/3+C/3/SS	54+4	66+4	74+4	82+4	96+4

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS



Hydraulic controlled roller helps with compaction and working uneven terrain



Hydraulic top link

ROTOR TYPE B



TOOTH B/3
(standard)



TOOTH B/3/HD
(option)



TOOTH G/3
(option)



TOOTH G/3/HD
(option)



TOOTH C/3/SS
(side scraper)