

ROAD PLANERS FOR SKID STEERS

RPL/SSL

Fixed tooth road planer for skid steers up to 135 hp.

The RPL/SSL is a road planer for skid steers from 60 to 135 hp, capable of milling up to 17 cm deep and is available in three widths of 45, 60 and 75 cm. The RPL/SSL is ideal for road preparation before adding a new layer of asphalt or concrete, or to simplify excavation operations. Self-leveling skids

and tilt ensure optimal results. Operational precision is ensured by the hydraulic drive system as well as practical depth and cutting indicators. The line is completed with teeth specifically designed for asphalt and concrete road surfaces. Available in the following versions: RPL/SSL/DT.



60-135 hp



Depth
17 cm



Extraordinary precision
it can work very close to the walls at left and at right

Available in DT version
the dual transmission guarantees optimal power supply and distribution across the entire width of the rotor



Cutting and depth indicators
for precise operation control



Tilt
for optimal results on uneven surfaces

Hydraulic drive system
for accurate positioning over the work area

Self-leveling skids
With independent hydraulic position control

STANDARD EQUIPMENT

Mechanical floating tilt system (tilt)	Anti-shock block valve with relief and anti-cavitation valves
Independent hydraulic skids control	Hydraulic hoses for connections
Mobile sides-frame	Interchangeable Hardox® antiwear skids plate
Hydraulic side shifting	Asphalt round bit teeth
Enclosed / anti-dust machine body	Cutting indicator
Working pressure control gauge	Diverter valve 12 V
860 cc fixed displacement hydraulic piston motor (RPL/SSL-45 and RPL/SSL-60)	940 cc fixed displacement hydraulic piston motor (RPL/SSL-75)
Direct drive motor transmission	565 cc fixed displacement hydraulic piston motor (RPL/SSL/DT)

OPTIONS

Multiple tooth options	Adaptor wiring
Water spray system WSS Basic	SAE attachment frame with integrated water tank
Roof mounted water tank kit for skid steer	Hydraulic floating tilt system

MODEL	RPL/SSL-45	RPL/SSL-60	RPL/SSL-75	RPL/SSL/DT-100	RPL/SSL/DT-125	RPL/SSL/DT-150
Engine (hp)	60-110	60-110	90-135	90-135	90-135	90-135
Requirements Flow (L/min)	100-155	100-155	120-170	120-200	120-200	120-200
Pressure (bar)	180-350	180-350	180-350	180-350	180-350	180-350
Working width (mm)	450	600	750	1000	1250	1500
Total width (mm)	1650	1650	1650	1650	1650	1650
Weight (kg)	900	950	1000	1150	1250	1350
Working depth (mm)	0-170	0-170	0-170	0-140	0-140	0-140
Rotor diameter (mm)	600	600	600	600	600	600
Tilting angle ±	8°	8°	8°	± 8°	± 8°	± 8°
Side shifting (mm)	560	560	560	560	560	560
N° picks type R	42	54	60	78	96	114

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS



Teeth for working on concrete



WSS Basic water injection system
to reduce dust and cool the teeth



Wiring adaptors
Wiring adaptors interface to allows a Plug & Play coupling with the most popular skid steers

ROTOR TYPE R



PICK R/44/A
(standard)



PICK R/44/C
(optional)