

## ROAD PLANERS FOR SKID STEERS

# RPL/SSL

Fixed tooth road planer for skid steers up to 135 hp.

The RPL/SSL is a road planer for skid steers from 60 to 135 hp, capable of milling up to 7 inches deep. The RPL/SSL is ideal for road preparation before adding a new layer of asphalt or concrete, or to simplify excavation operations. Self-leveling skids and tilt ensure optimal

results. Operational precision is ensured by the hydraulic drive system as well as practical depth and cutting indicators. The line is completed with teeth specifically designed for asphalt and concrete road surfaces. Available in the following versions: RPL/SSL/DT.



60-135 hp



Depth  
7 in



**Tilt**  
for optimal results on uneven surfaces

**Hydraulic side shifting**  
for accurate positioning over the work area

**Self-leveling skids**  
With independent hydraulic position control

**Extraordinary precision**  
it can work very close to the walls at left and at right



**Available in DT version**  
the dual transmission guarantees optimal power supply and distribution across the entire width of the rotor

**Cutting and depth indicators**  
for precise operation control



## MAIN OPTIONS



**Teeth for working on concrete**



**WSS Basic water injection system**  
to reduce dust and cool the teeth



**Wiring adaptors**  
Wiring adaptors interface to allow a Plug & Play coupling with the most popular skid steers

## STANDARD EQUIPMENT

Mechanical floating tilt system (tilt)	Anti-shock block valve with relief and anti-cavitation valves
Independent hydraulic skids control	Hydraulic hoses for connections
Mobile sides-frame	Interchangeable Hardox® antiwear skids plate
Hydraulic side shifting	Asphalt round bit teeth
Enclosed / anti-dust machine body	Cutting indicator
Working pressure control gauge	Diverter valve 12 V
860 cc fixed displacement hydraulic piston motor (RPL/SSL-45 and RPL/SSL-60)	940 cc fixed displacement hydraulic piston motor (RPL/SSL-75)
Direct drive motor transmission	565 cc fixed displacement hydraulic piston motor (RPL/SSL/DT)

## OPTIONS

Multiple tooth options	Adaptor wiring
Water spray system WSS Basic	SAE attachment frame with integrated water tank
Roof mounted water tank kit for skid steer	Hydraulic floating tilt system

MODEL	RPL/SSL-45	RPL/SSL-60	RPL/SSL-75	RPL/SSL/DT-100	RPL/SSL/DT-125	RPL/SSL/DT-150
<b>Engine (hp)</b>	60-110	60-110	90-135	90-135	90-135	90-135
<b>Requirements Flow (gal/min)</b>	26-41	26-41	32-45	32-53	32-53	32-53
<b>Pressure (PSI)</b>	2600-5080	2600-5080	2600-5080	2600-5080	2600-5080	2600-5080
<b>Working width (in)</b>	18	24	30	39	49	59
<b>Total width (in)</b>	65	65	65	65	65	65
<b>Weight (lbs)</b>	1990	2100	2200	2535	2866	2976
<b>Working depth (in)</b>	0-7	0-7	0-7	0-5.5	0-5.5	0-5.5
<b>Rotor diameter (in)</b>	23.6	23.6	23.6	23.6	23.6	23.6
<b>Tilting angle ±</b>	8°	8°	8°	± 8°	± 8°	± 8°
<b>Side shifting (in)</b>	22	22	22	22	22	22
<b>N° picks type R</b>	42	54	60	78	96	114

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

## ROTOR TYPE R



**PICK R/44/A**  
(standard)



**PICK R/44/C**  
(optional)