

## STUMP CUTTERS

# SCH/GT

### Stump cutter for tractors, for rows of stumps.

The SCH/GT model is a stump cutter designed for shredding rows of stumps, for example in poplar groves or eucalyptus fields. This head is perfect for 180-350 hp tractors and has a working depth of 60 cm. It also comes with internal Hardox® wear plates. Its dual clutch transmission provides superior performance and excellent power management.

SCH/GT models (except for the SCH/GT-75 model) have a hydraulic side shift system that lets the operator adjust to the working area without having to make additional maneuvers with the tractor. It is extremely easy to use and shreds stumps uniformly.



180-350 hp



Depth 60 cm



**Dual transmission with side gearbox** increase power delivery to the rotor



**Hydraulic side shifting** allows the stump cutter to move easily, quickly, and accurately while working close to plants and crops without damaging them



#### STANDARD EQUIPMENT

Hydraulic side shifting (excluding SCH/GT/DT-65)	Gearbox with freewheel
Enclosed machine body	PTO shaft with cam clutch
Inside lateral protection	Bolted-on rotor shafts (in forged steel)
Protection chains	Welded steel counter-blades
Transmission with side gearbox	Supporting service leg

#### OPTIONS

Multiple tooth options	Hydraulic top link
------------------------	--------------------

MODEL	SCH/GT/DT-65	SCH/GT/DT-75
<b>Tractor</b> (hp)	180-300	200-350
<b>PTO</b> (rpm)	1000	1000
<b>Working width</b> (mm)	730	810
<b>Total width</b> (mm)	1800	1980
<b>Weight</b> (kg)	2900	3690
<b>Rotor diameter</b> (mm)	900	1100
<b>Max working depth</b> (mm)	500	600
<b>No. teeth</b> type A/3+MH/3	28+4	34+4

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

#### MAIN OPTIONS



Hydraulic top link

#### ROTOR TYPE A



**TOOTH A/3**  
(standard)



**TOOTH A/3/HD**  
(option)



**TOOTH F/3**  
(option)



**TOOTH MH/3**  
(side scraper)