

## FORESTRY MULCHERS FOR EXCAVATORS

# PMM/EX

### Mulcher with hammer/flail rotor for excavators.

The PMM/EX is a flail mower used to mulch underbrush, grass and bushes. It is equipped with a variable manual displacement hydraulic piston motor that can be set to the carrier's hydraulic specifications. The stronger roller supports (optional) ensure the best performance and

maximum reliability on difficult terrain. The flow control valve ensures minimal setup of the mulcher without adjustments or modifications to the hydraulic system of the excavator.

 15-38 gal/min

 Ø 3 in max

 6-13 t



**Steel counter-blades**  
helps mulch material into  
a smaller final size



**Self-cleaning support roller**

**Enclosed machine body**



**Stronger bearings  
for the support roller**



#### STANDARD EQUIPMENT

32/65 cc variable manual displacement hydraulic piston motor	Bulkhead for hydraulic connections
Flow control system valve	Rear hood with mechanical adjustment
Safety and anticavitation valve	Adjustable skids
Enclosed / anti dust machine body	Self levelling protection flaps
Motor enclosed in the frame	Welded counterblades
Belt transmission	Self cleaning rear roller with integrated skids


#### OPTIONS

Customized setting hydraulic motor	Attachment plate with self levelling device
Customized attachment bracket with pins	Possibility to have the rotor equipped with PML hammers or Y-flails
Not supplied with hoses	Case drain required

MODEL	PMM/EX-100	PMM/EX-125	PMM/EX-150
<b>Flow rate</b> (gal/min)	15-38	15-38	15-38
<b>Pressure</b> (PSI)	2611-5076	2611-5076	2611-5076
<b>Excavator weight</b> (t)	6-13	6-13	6-13
<b>Working width</b> (in)	42	51	61
<b>Weight</b> (lbs)	1156	1333	1511
<b>Rotor diameter</b> (in)	17.3	17.3	17.3
<b>Max shredding diameter</b> (in)	3	3	3
<b>No. hammers</b> type PMM	12	16	18
<b>No. flails</b> type Y/3	12	16	18

*Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.*

#### MAIN OPTIONS



**Customized setting hydraulic motor**



**Attachment plate with self levelling device**  
to adapt to all types of terrain



**Possibility to have the rotor equipped with PML hammers or Y-flail**



**HAMMER PMM**  
(standard)



**FLAIL Y/3**  
(option)