

## STUMP CUTTERS FOR EXCAVATORS

# SCM/EX

### Disc stump cutters for excavators.

The SCM/EX is designed to remove stumps quickly and easily. The front hood with hydraulic adjustment and front fixed thumb are designed to move around previously cut material.

This feature combined with the reliability and resistance of the disc allows for the best performance and safety while the stumps are being removed.



34-49 gal/min



14-24 t



Access panel

**VT motor**  
to increase performance  
and reduce operating costs



Front hydraulic hood with bolt-on chains/protection plates



**Motor enclosed in frame**  
protected from dirt and damage

**Adjustable supporting service stand**  
for storing the machine when not in use

#### STANDARD EQUIPMENT

160/108cc variable torque hydraulic piston motor	Bulkhead for hydraulic connections
Flow control system valve	Hydraulic front hood
Safety and anticavitation valve	Screwed protection chains
Enclosed / anti dust machine body	Bolt-on chains / protection plates
Motor enclosed in the frame	Supporting service leg
Poly Chain® Belt Transmission	

#### OPTIONS

Customized setting hydraulic motor	Customized attachment bracket with pins
Diverter valve (plug & play)	Customized attachment bracket with pins and leg
Rear fixed heel	
Not supplied with hoses	Case drain required

#### MODEL


MODEL	SCM/EX/VT
<b>Flow rate</b> (gal/min)	34-49
<b>Pressure</b> (PSI)	3200-5080
<b>Excavator weight</b> (t)	14-24
<b>Total width</b> (in)	31
<b>Weight</b> (lbs)	2425
<b>Rotor diameter</b> (in)	32
<b>No. teeth</b> type M/1+M/2+M/3+M/4	12+3+12+3

*Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.*

#### MAIN OPTIONS



Front fixed thumb



Customized setting hydraulic motor



Customized attachment bracket with fixed thumb



Customized attachment bracket

#### DISC ROTOR



TOOTH M/3 (standard)



TOOTH M/1 (standard)



TOOTH M/4 (standard)



TOOTH M/2 (standard)